

HCL2GV / HCW2GV

Network TDN Low-Light WDR
2MP Box Camera



HD ONVIF | S G Q

| OPERATIONAL | |
|--------------------------------|---|
| VIDEO STANDARD | NTSC/PAL |
| SCANNING SYSTEM | Progressive scan |
| IMAGE SENSOR | 1/2.8" 2 Megapixel progressive scan CMOS |
| NUMBER OF PIXELS (H x V) | 2MP - 1920x1080 |
| MINIMUM ILLUMINATION | Colour: 0.001Lux @f/1.6, B/W: 0.001Lux @f/1.6 |
| S/N RATIO | 50 db minimum |
| ELECTRONIC SHUTTER SPEED | Auto/Manual, 1/3-1/10000s |
| DAY/NIGHT | Mechanical ICR (ON / OFF / AUTO selectable) |
| BACKLIGHT COMPENSATION | BLC / HLC / WDR / SAC(Scene Adaptive Control) |
| WIDE DYNAMIC RANGE (WDR) | HCL2GV: 140dB (50/60fps off) HCW2GV: 120dB (50/60fps off) |
| WHITE BALANCE | Auto/Natural/Street Lamp/Outdoor/Manual/Customize Region |
| GAIN CONTROL | Auto/Manual |
| NOISE REDUCTION | 3D Noise Reduction (ON / OFF selectable) |
| PRIVACY MASKING | Up to 4 configurable areas |
| ELECTRONIC IMAGE STABILIZATION | HCW2GV: Not supported HCL2GV: ON/OFF |
| DEFOG | Auto/Manual/Off |
| LENS | Option, support DC-Iris |
| AUDIO/TWO-WAY | Line In/Out, 1 built-in Mic |
| ALARM INPUT/OUTPUT | 2 in / 1 out |
| ANALOG OUTPUT SUPPORT | Supported |
| ETHERNET | HCW2GV: RJ-45 (10/100 Base-T) HCL2GV: RJ-45 (100/1000 Base-T) |
| IP SPECIFICATIONS | |
| VIDEO COMPRESSION | H.265+, H.265, H.264 and MJPEG bit rate control (CBR and VBR) |
| RESOLUTION | 16:9 1080p (1920x1080)/ 720p (1280x720) |
| | 4:3 1.3M (1280x960)/VGA (640x480) |
| | OTHER D1 (704x576/704x480)/ CIF (352x288/352x240) |
| FRAME RATE | MAIN STREAM 1080P (1~50/60fps WDR off) |
| | SUB STREAM D1 (1~50/60fps WDR off) |
| | THIRD STREAM HCL2GV: 1080P (1~50/60fps WDR off) HCW2GV: 1080P (1~25/30fps) |
| | HCW2GV: Simultaneous Main stream and Third stream at 1080P (Main stream +Third stream <=68fps, WDR off, 2nd stream off) HCL2GV: Simultaneous Main stream and Third stream at 1080P (Main stream at 50/60fps WDR off, Third stream at 50/60fps WDR off) |
| AUDIO COMPRESSION | G.711a/ G.711Mu/ AAC/G.726 |
| AUDIO STREAM | Full duplex, simplex |
| SUPPORTED WEB BROWSERS | IE11/Chrome(with application)/Firefox(earlier than 52.0 version) |
| SUPPORTED OS | Windows® 7 32-bit/64-bit; Windows® 10 32-bit/64-bit |
| SUPPORTED PROTOCOLS* | HTTP, HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; SNMP |
| COMPATIBILITY | ONVIF Profile S, G and Q |
| MAXIMUM USERS ACCESS | 20 users |

* Some development may be required in specific user cases to support some of these protocols in the field as they mature over time.

| IP SPECIFICATIONS (CONT.) | |
|--|---|
| SECURITY | User account and password protection HTTPS, IP Filter, IEEE 802.1x, Digest authentication, User access log, TLS1.2, AES-256, SSH/Telnet closed, FTP disabled, PCI-DSS compliance, Hardware chipset for private key |
| HEAT MAP | HCL2GV: Support |
| BUILT-IN ALARM & EVENT | EVENT TYPE HCW2GV: Motion Detection/Video Tampering/Face Detection/SD Card Error/SD Card Capacity Warning/Audio Detection/ Object Abandoned/Object Missing/Tripwire/Intrusion HCL2GV: Motion Detection/Video Tampering/Face Detection/SD Card Error/SD Card Capacity Warning/Audio Detection/Object Abandoned/Object Missing/People counting |
| | EVENT LINKAGE Recording on SD card, Relay output, Email, Snapshot |
| | EVENT OUTPUT ONVIF, ISOM |
| UPLOADABLE VIDEO ANALYTICS (HCL2GV ONLY) | BASIC Trigger line/Intrusion/Loitering available now (Please download from www.honeywellvideo.com. Free of Charge, but please email to VAlicensing@Honeywell.com to get license.) |
| | ADVANCED LICENSED ANALYTICS IntrusionTrace/LoiterTrace for advanced applications coming soon. (Need to purchase separately) |
| | ANALYTICS OUTPUT ISOM event output, Metadata |
| MICRO SD | Micro SDHC Capacity Max 32GB Micro SDXC Capacity Max 128GB |
| MICRO SD FUNCTION | <ul style="list-style-type: none"> Event trigger recording Continuous and scheduled recording Automatic recording when network fails |
| LANGUAGES SUPPORTED | English, Arabic, Czech, Dutch, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Turkish |
| ELECTRICAL | |
| POWER SUPPLY | PoE(802.3af) Class 0/12VDC/24VAC |
| LONG DISTANCE POE SUPPORT | 3X POE (300m @100Mbps) |
| AC FREQUENCY | 50/60 Hz |
| POWER CONSUMPTION | HCW2GV: Max 10W HCL2GV: Max 9.5W |
| AUXILIARY POWER SUPPLY | 2.0W, DC12V (+/-5%) |
| MECHANICAL | |
| DIMENSIONS | 125.0x75.8x69.0 mm (4.92x2.98x2.72 in.) |
| WEIGHT | HCW2GV: Product weight: 535g (1.18lb); Package Weight: 756g (1.67lb) HCL2GV: Product weight: 534g (1.18lb); Package Weight: 755g (1.66lb) |
| CONSTRUCTION | Die-cast aluminum housing with powder coat |
| CONSTRUCTION COLOUR | RAL 9003 (White) and RAL 7022 (Grey) |
| ENVIRONMENTAL | |
| OPERATING TEMPERATURE | -30°C to 60°C (-22°F to 140°F) |
| RELATIVE HUMIDITY | 0% to 95%, non-condensing |
| REGULATORY | |
| EMISSIONS | FCC Part 15, CE (EN 55032); Complies with RCM (AS/NZS) |
| IMMUNITY | CE (EN 50130-4) |
| SAFETY | North America UL Listed to UL/CSA 60950-1, CE (EN 60950-1) |
| ROHS | EN50581 |

Network TDN Low-Light WDR 2MP Box Camera


RECOMMENDED ACCESSORIES

SYSTEM INTEGRATION

ONVIF support and open API software integration. Refer to www.onvif.org for the ONVIF specification and the Honeywell Open Technology Alliance website (<http://www.security.honeywell.com/hota/>) to learn more about our open and integrated solutions.



REAR VIEW



| | |
|----|---------------------------------------|
| G | GND |
| TX | RS232 (TX) |
| RX | RS232 (RX) |
| B | RS485 B (Control outside PTZ) |
| A | RS485 A (Control outside PTZ) |
| NA | Outside IR Sensor Signal (For IR Cut) |
| I1 | Alarm In 1 |
| I2 | Alarm In 2 |
| O1 | Alarm Out (Normal Open) |
| P | AUX Power Output (DC12V/2W) |

HOUSING AND MOUNTS

| | | |
|--------------|--|---|
| HLM105V42MPD | | 12 Megapixel 4K, 10.5 – 42 mm Lens |
| HLM5V50MPDE | | 6MP, 1/1.2.7", F1.6, 5.0 – 50mm CS lens |
| HLM37V16MPD | | 12 Megapixel 4K, 3.7 – 16 mm Lens |
| HLM27V12MPD | | 4 MP, 1/2.7", F1.6, 2.7 – 12.0 mm CS Lens |
| HBC5WT-2 | | Box Camera Wall Mount |
| HPOE3X | | 3X Long Distance POE Switch |
| HLR1001 | | IP over Coax Converter |

ORDERING

| | |
|--------|---|
| HCL2GV | Network TDN Intelligent Ultra WDR Box Camera, 1/2.8" 2 Megapixel progressive scan CMOS, PoE, H.265. |
| HCW2GV | Network TDN Low Light WDR Box Camera, 1/2.8" 2 Megapixel progressive scan CMOS, PoE, H.265. |

For more information


www.honeywell.com/security/uk

Honeywell Security

Aston Fields Road
Whitehouse Industrial Estate
Runcorn, Cheshire, WA7 3DL
United Kingdom
Tel: +44 (0)8448 000 235

Honeywell Security Office
Emaar Business Park, Sheikh Zayed Road
Building No. 2, 2nd floor, 201
Post Office Box 232362
Dubai, United Arab Emirates
Tel: +971 44541704
www.honeywell.com

DIMENSIONS



ONVIF and the ONVIF logo are trademarks of ONVIF Inc. Honeywell reserves the right, without notification, to make changes in product design or specifications.

HSV-HC2GV-01-UK(0618)DS-Z
© 2018 Honeywell International Inc.

Honeywell