

AXIS P1455-LE Network Camera

Versatile, feature-rich 2 MP surveillance

AXIS P1455-LE offers excellent image quality in HDTV 1080p at up to 60 fps. Featuring Axis Lightfinder 2.0 and Axis Forensic WDR it delivers true colors and great detail in challenging light or near darkness. AXIS Object Analytics lets you detect and classify humans and vehicles. And, with edge-to-edge technology, it offers smart pairing functionality including two-way audio with Axis Network Speakers. Motion-adaptive exposure significantly reduces the motion blur from approaching or nearby objects, and OptimizedIR enables surveillance in pitch darkness. Furthermore, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis products on your network.

- > [Lightfinder 2.0 and Forensic WDR](#)
- > [OptimizedIR up to 40 m \(131 ft\)](#)
- > [AXIS Object Analytics](#)
- > [Enhanced security features](#)
- > [Zipstream with support for H.264/H.265](#)



AXIS P1455-LE Network Camera

| | | |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Camera | | Storage: disruption, recording System: system ready Time: recurrence, use schedule |
| Image sensor | 1/2.8" progressive scan RGB CMOS | Event actions Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, day/night mode |
| Lens | Varifocal, 3–9 mm, F1.6 Horizontal field of view 114°–37° Vertical field of view 58°–21° Varifocal, Remote focus and zoom, P-Iris control, IR corrected | |
| Day and night | Automatically removable infrared-cut filter | Data streaming Event data |
| Minimum illumination | Color: 0.07 lux, at 50 IRE F1.6 B/W: 0.01 lux, at 50 IRE F1.6 0 lux with IR illumination on | |
| Shutter speed | 1/66500 s to 2 s | Built-in installation aids Pixel counter, remote zoom (3x optical), remote focus, auto rotation |
| Video | | Analytics |
| Video compression | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG | Compute capabilities Machine learning processing unit (MLPU) |
| Resolution | 1920x1080 to 160x90 | AXIS Object Analytics Object classes: humans, vehicles Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event |
| Frame rate | With Forensic WDR: Up to 25/30 fps (50/60 Hz) in all resolutions No WDR: Up to 50/60 fps (50/60 Hz) in all resolutions | |
| Video streaming | Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator | Applications Included AXIS Object Analytics AXIS Video Motion Detection, active tampering, shock detection Supported AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap |
| Multi-view streaming | Up to 8 individually cropped out view areas | |
| Image settings | Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, defogging, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks, motion-adaptive exposure Scene profiles: forensic, traffic overview | General |
| Pan/Tilt/Zoom | Digital PTZ, digital zoom | |
| Audio | | Casing IP66/IP67-, NEMA 4X-, and IK10-rated casing Polycarbonate blend and aluminium Color: white NCS S 1002-B |
| Audio streaming | Audio in, simplex, two-way audio via edge-to-edge technology | Sustainability PVC free |
| Audio encoding | 24bit LPCM, AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate | Memory 1024 MB RAM, 512 MB Flash |
| Audio input/output | External microphone input or line input, network speaker pairing | Power Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical: 7.7 W, max 12.95 W |
| Network | | Connectors Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T 3.5 mm mic/line in Terminal block for 1 supervised alarm input and 1 output (12 V DC output, max. load 25 mA) |
| Security | Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, Axis Edge Vault with Axis device ID | IR illumination Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 40 m (131 ft) or more depending on the scene |
| Supported protocols | IPv4, IPv6 USGv6, HTTP, HTTPS ^a , HTTP/2, SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, MQTT, Syslog | Storage Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com |
| System integration | | Operating conditions -40 °C to 60 °C (-40 °F to 140 °F) Maximum temperature according to NEMA TS2 (2.2.7): 74 °C (165 °F) Start-up temperature: -30 °C Humidity 10–100% RH (condensing) |
| Application Programming Interface | Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S and ONVIF [®] Profile T, specification at onvif.org | Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing) |
| Onscreen controls | Day/night shift Defogging Wide dynamic range Video streaming indicator IR illumination | Approvals EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55035, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IS 13252, IEC 62471 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9) Network NIST SP500-267 |
| Event conditions | Analytics Detectors: live stream accessed, video motion detection, audio detection, day/night mode, shock detection, tampering Hardware: network, temperature Input Signal: digital input port, manual trigger, virtual inputs | |

| | |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight | With weather shield: 1 kg (2.2 lb) |
| Dimensions | Ø132 x 260 mm (Ø5 3/16 x 10 1/4 in) |
| Included accessories | Installation guide, Windows® decoder 1-user license, drill hole template, connector kit, mounting bracket, Torx® L-keys AXIS Weather Shield L |
| Optional accessories | AXIS T94F01M J-Box/Gang Box Plate, AXIS T91A47 Pole Mount, AXIS T94P01B Corner Bracket, AXIS T94F01P Conduit Back Box, AXIS Weather Shield K, Axis PoE Midspans For more accessories, see axis.com |
| Video management software | AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at axis.com/vms |

Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese

Warranty 5-year warranty, see axis.com/warranty

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

Environmental responsibility:

axis.com/environmental-responsibility