

AXIS Q2901-E Temperature Alarm Camera

For remote temperature monitoring

The outdoor-ready, bullet-style AXIS Q2901-E delivers thermal imaging in 336x256 resolution. AXIS Q2901-E supports up to six temperature alarm zones that can be used to trigger an alarm. It offers two kinds of alarms triggered by a deviation of the temperature: if the temperature goes beyond a set limit, or if it increases too rapidly. The spot temperature functionality is used to view the temperature of a particular area. Isothermal palettes highlight temperature-spans in the image, making it easier to visualize hot spots to identify overheated equipment or areas.

- > [Temperature alarm](#)
- > [Isothermal palettes](#)
- > [Spot temperature reading](#)
- > [High performance intelligent video](#)



AXIS Q2901-E Temperature Alarm Camera

Models	AXIS Q2901-E 9 mm AXIS Q2901-E 19 mm	Built-in installation aids	Pixel counter
Camera		Data streaming	Event data
Image sensor	Uncooled Micro bolometer 336x256 pixels, Pixel size 17 µm, Spectral range: 8-14 µm	General	
Lens	9 mm: F 1.25, 35° view ^a , min. focus distance: 2.1 m (78.7 in) 19 mm: F 1.25, 17° view ^a , min. focus distance: 9.5 m (354.3 in)	Casing	IP66-, IP67- and NEMA 4X-rated metal casing (aluminium) with integrated dehumidifying membrane and a germanium window Color: White NCS S 1002-B. For repainting instructions and impact on warranty, contact your Axis partner
Sensitivity	NETD < 50 mK	Memory	256 MB RAM, 128 MB Flash
Thermography		Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3, max. 10 W, 8-20 V DC, max. 11 W or 20-24 V AC 50-60 Hz, max. 15 VA, Power supply not included
Object temperature range	-40 °C to 550 °C (-40 °F to 1022 °F)	Connectors	RJ45 10BASE-T/100BASE-TX PoE, Terminal block for power Eight circuit PCB header for two configurable inputs/outputs and audio
Temperature accuracy	Below 100 °C (212 °F): +/- 5 °C (+/-9 °F) accuracy Below 150 °C (302 °F): +/- 5% accuracy Above 150 °C (302 °F): +/- 20% accuracy	Edge storage	SD card slot supporting microSD/microSDHC/microSDXC cards (card not included). Support for recording to dedicated network-attached storage (NAS). For SD card and NAS recommendations, see www.axis.com
Video		Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Humidity 10-100% RH (condensing)
Video compression	H.264 (MPEG-4 Part 10/AVC) Main and Baseline Profile, Motion JPEG	Approvals	Emission and immunity: EN 55022 Class B, EN 50121-4, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC part 15 Subpart B Class A, FCC part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, ITE, C-Tick AS/NZS CISPR22 Class B, KCC KN22 Class B, KN-24 Safety: IEC/EN/UL 60950-1, IEC/EN/UL 60950-22 Environment: EN 50581, IEC 60529 IP66, IEC 60529 IP67, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78
Resolutions	Sensor is 336x256. Image can be scaled up to 720x576	Weight	2 kg (4.4 lb)
Frame rate	Up to 8.3 fps	Included accessories	Installation Guide, Windows decoder 1-user license, AVHS Authentication key, AXIS Video Motion Detection 3, AXIS Connector A 2-pin 5.08 Straight Allen key, RJ45 network cable 5 m (16 ft), Wall and Ceiling Mount Bracket
Video streaming	3 individual streams ^b in H.264 and Motion JPEG: simultaneous, individually configured streams in max. resolution at 8.3 fps, Controllable frame rate and bandwidth. VBR/CBR H.264	Optional accessories	AXIS T8120/T8123-E midspans, Network cable couplers, AXIS T8129 PoE Extender, AXIS T8604 Media Converter, AXIS T8640 Ethernet over Coax Adapter PoE+, AXIS PS24 Mains Adapter, AXIS T8006 PS12 Power Supply, AXIS T8414 Installation Display AXIS T94G01P Conduit Back Box, AXIS T91A47 Pole Mount, AXIS T94P01B Corner Bracket, AXIS T98A17-VE Video Surveillance Cabinet, AXIS Multicable A I/O Audio Power
Image settings	Sharpness, Automatic gain control, Exposure zones, Gain, Rotation, Palette, Isothermal palette, Compression, Mirroring, Text and image overlay and Privacy masks	Video management software	AXIS Camera Companion (included), AXIS Camera Station and video management software from Axis' Application Development Partners (not included). For more information, see www.axis.com/products/video/software
Audio		Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Audio streaming	Two-way		
Audio compression	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Configurable bit rate		
Audio input/output	External microphone or line input, line output		
Network			
Security	Password protection, IP address filtering, HTTPS ^c encryption, IEEE 802.1X ^c network access control, Digest authentication, User access log, Centralized certificate management		
Supported protocols	IPv4/IPv6, HTTP, HTTPS ^c , SSL/TLS ^c , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3(MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH		
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection		
Analytics	Video motion detection, Active tampering alarm, Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3.0, AXIS Cross Line Detection and third-party applications, see www.axis.com/acap		
Event triggers	Intelligent video, Temperature detection, Hardware temperature, Edge storage events, Shock detection, Time scheduled		
Event actions	File upload: FTP, HTTP, network share and email Notification: email, HTTP and TCP Status LED, Text overlay, SNMP, Pre- and post-alarm video buffering, Video recording to edge storage, Network share, PTZ preset, Guard tour		

- a. Horizontal angle of view
b. Individual palette cannot be set per video stream
c. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

More information is available at www.axis.com