

SNC-EMX30/EMX30R

Minidome indoor Full HD camera with Exmor Sensor and 3-10mm Easy Focus/ Easy Zoom lens

SONY

- Superior 1080p image at 30 fps with Easy Focus/ Easy Zoom capability
- Essential Video Analytics - detect, track and analyze objects, providing alerts in response to predefined alarm rules
- Latest Data Security Technology including Trusted Platform Module
- Intelligent bitrate management techniques and Intelligent Dynamic Noise Reduction combined with H.265 video compression
- True Day/ Night
- IR version (SNC-EMX30R) with a built-in active infrared illuminator (30m, 98 ft. viewing distance)



KEY FEATURES

- Ideal for indoor use. The pan/tilt/rotation mechanism allows installers to select the exact field of view. With Easy Focus/ Easy Zoom the zoom can be changed without opening the camera, using the automatic lens wizard. This makes it easy for an installer to accurately zoom and focus the camera for both day and night operation.
- Built-in Essential Video Analytics allow the camera to reliably detect, track and analyze objects, providing alerts in response to predefined alarm.



With latest Essential Video Analytics (EVA)

- The low-noise image and the efficient H.265 compression technology provide clear images while reducing bandwidth and storage by up to 80% compared to standard H.264 cameras.

- The on-board Trusted Platform Module (TPM) and Public Key Infrastructure (PKI) support, guarantee superior data security and protection from malicious attacks. The 802.1x network authentication with EAP/ TLS, supports TLS 1.2 with updated cipher suites including AES 256 encryption.
- The integrated gyro/accelerometer sensor automatically corrects the image orientation in steps of 90° if the camera is mounted at right angles or upside down.
- True Day/Night switching - The camera incorporates mechanical filter technology for vivid daytime color and exceptional night-time imaging while maintaining sharp focus under all lighting conditions.
- Edge Recording- Insert an optional memory card and store up to 2TB of local alarm recording. Pre-alarm recording reduces network bandwidth.
- The camera conforms to ONVIF Profiles S, T and G, which guarantees interoperability between network video products regardless of manufacturer.



Technical specifications

Power	
Power Supply	+12 VDC ±5%, 24 VAC ±10% or PoE (48 VDC nominal)
Power Consumption	SNC-EMX30: 6 W max., SNC-EMX30R: 9 W max. (DC)
PoE	IEEE 802.3af (802.3 at Type 1) Power level: Class 3
Sensor	
Type	1/2.9-inch Exmor CMOS
Effective pixels	1920 (H) x 1080 (V); 2MP (approx.) FHD
Video performance – Minimum Illumination	
(F1.3, AGC On, 1/25 s, 30 fps, 30 IRE)	
Color	0.12 lx
B/W	0.02 lx
IR LED on	0.0 lx
Video performance – Dynamic range	
Wide Dynamic Range	85 dB (measured according IEC 62676 Part 5)
Video streaming	
Video compression	H.265; H.264; M-JPEG
Streaming	Multiple configurable streams in H.264 or H.265 and M-JPEG, configurable frame rate and bandwidth
Encoder Regions/Region of interest (ROI)	Up to 8 areas with encoder quality settings per area
Video resolution (H x V)	
Maximum Video resolution (H x V)	1920 x 1080
Video functions	
Day/Night	Color, Monochrome, Auto (adjustable switch points)
Adjustable picture settings	Contrast, Saturation, Brightness
White Balance	2500 to 10000K, 4 automatic modes (Basic, Standard, Sodium vapor, Dominant color), Manual mode and Hold mode
Shutter	Automatic Electronic Shutter (AES); Fixed [1/25][30] to 1/15000 selectable; Default shutter
Backlight compensation	On /off / Intelligent Auto Exposure (BLC)
Noise reduction	Intelligent Dynamic Noise Reduction with separate temporal and spatial adjustments
Sharpness	Sharpness enhancement level selectable
Intelligent defog	Intelligent Defog automatically adjusts parameters for best picture in foggy or misty scenes (switchable)
Privacy Masking	Eight independent areas, fully programmable
Video Analytics	Essential Video Analytics
Other functions	Image mirror, Image flip, Pixel counter, Video watermarking, Display stamping, Location
Camera rotation	Automatic detection with manual override (0° / 90° / 180° / 270°)
Optical	
Lens type	3 to 10 mm Easy Focus/ Easy Zoom lens, IR corrected DC Iris F1.3 - 360
Lens mount	Board mounted
Adjustment	Motorized zoom/focus
Iris control	Automatic iris control
Day/Night	Switched mechanical IR filter
Horizontal field of view	34° - 101°
Vertical field of view	19° - 54°
Night vision (IR version only)	
Distance	30 m (98 ft)
LED	10 LED high efficiency array, 850 nm
IR intensity	Adjustable
Audio	
Audio input	Built-in microphone (can be permanently disabled)
Audio line in	0.707 Vrms max, 10 kOhm typical, jack connector
Audio line out	0.707 Vrms max, 16 kOhm typical, jack connector
Audio streaming standard	G.711, 8 kHz sampling rate L16, 16 kHz sampling rate AAC-LC, 48 kbps at 16 kHz sampling rate AAC-LC, 80 kbps at 16 kHz sampling rate
Signal-to-Noise Ratio	>50 dB
Audio Streaming	Full-duplex / half duplex
Local storage	
Internal RAM	60 s pre-alarm recording
Memory card slot	Supports up to 32 GB microSDHC / 2 TB microSDXC card. (A memory card of Class 6 or higher is recommended for HD recording)
Recording	Continuous recording, ring recording, alarm / events /schedule recording

Software	
Unit discovery	SNC Toolbox
Unit configuration	Via web browser or SNC Toolbox
Firmware update	Remotely programmable
Software viewing	Web browser; or third party software
Latest firmware and software	pro.sony/support/software
Network	
Protocols	IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/ RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, SMTP, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox™, CHAP, digest authentication
Encryption	TLS1.0/1.2, AES128, AES256
Ethernet	10/100 Base-T, auto-sensing, half/full duplex
Connectivity	Auto-MDIX
Interoperability	ONVIF Profile S, G and T
Mechanical	
3-axis adjustment (pan/tilt/rotation)	350° / 130° / 330°
Dimensions (Ø x H)	148 x 104 mm (5.81 x 4.09 in)
Weight	530 g (1.17 lb)
Environmental	
Operating temperature (continuous)	-20 °C to +50 °C (-4 °F to +122 °F)
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Humidity	5% to 93% relative humidity (non condensing)
Accessories	
Wall mount bracket	UNI-UMB1
Pendant mount cap	UNI-MDPEM600

DIMENSIONS

