

# Compact Day/Night Camera VBC-265 Series

www.boschsecurity.com



**BOSCH**  
Invented for life



Advantage Line

The VBC-265 Day/Night Camera is a professional surveillance day/night camera that incorporates 10-bit digital signal processing. The camera parameters can be set individually and a Lens Wizard ensures accurate back focusing at all times. The camera has enhanced night viewing compared to normal color cameras. The IR filter switches to monochrome automatically. A through-the-lens IR detector enhances the monochrome mode stability. The automatic black level enhances contrast by compensating for reduced contrast (glare, fog, mist, etc.).

## Features

- ▶ Superior picture quality
- ▶ Outstanding resolution (540 TVL)
- ▶ IR sensitivity at night
- ▶ Auto detection of lens
- ▶ Easy to install

## 2 | Compact Day/Night Camera VBC-265 Series

### Technical specifications

Electrical			
Model No.	Rated Voltage	Range	
VBC-265-11 (C)	12 VDC	10.8-39 VDC	
	24 VAC 50 Hz	12-28 VAC 45-65 Hz	
VBC-265-51 (C)	230 VAC 50 Hz	85-265 VAC 45-65 Hz	
Rated Voltage	12 VDC		
(VBC-265-11, VBC-265-11C)	24 VAC, 50 Hz		
Rated Voltage	230 VAC, 50 Hz		
(VBC-265-51, VBC-265-51C)			
Power Consumption	4 W		
CCD Type	1/3-inch interline		
Active Pixels	752 x 582		
Horizontal Resolution	540 TVL		
Day/Night	Color, Mono, Auto		
Dynamic range	60 db (10-bit image processing)		
Signal-to-Noise Ratio	> 50 dB		
BLC	On (center window weighted), Off		
Gain	20 dB max.		
White Balance	ATW (2500 - 10000 K), AWB hold, Manual WB selectable		
Shutter	Auto (1/50 to 1/150000), fixed, flickerless		
Auto Black	Automatic, Continuous, Off		
Synchronization	Internal, Line Lock selectable		
Lens Mount	CS (maximum lens protrusion 5 mm, 0.2 in), C-mount compatible with adapter ring		
Lens Types	Manual, DC iris and Video iris auto-detect with override  DC-iris drive: max. 50 mA continuous Video-iris: 11.5 ± 0.5 VDC, max 50 mA continuous		
Remote Control	Bilinx coaxial communication		
Camera ID	16 character editable string, position selectable		
Alarm Input (TTL)	+5 V nominal, +40 VDC max		
Alarm Output	Monochrome		
Alarm Output Relay	Max. 30 VAC or +40 VDC, Max 0,5 A continuous, 10 VA		
Video Output	1 Vpp, 75 Ohm		
Sensitivity			
(3200 K, scene reflectivity 89%, F1.2)			
	Full video (100 IRE)	Usable picture (50 IRE)	Usable picture (30 IRE)
Color	2.6 lx (0.26 fc)	0.65 lx (0.065 fc)	0.30 lx (0.03 fc)
Mono	1.04 lx (0.104 fc)	0.26 lx (0.026 fc)	0.012 lx (0.0012 fc)

Mechanical	
Dimensions (H x W x L)	58 x 66 x 122 mm (2.28 x 2.6 x 4.8 in) without lens
Weight	450 g (0.99 lbs) without lens
Color	RAL 7035 Light Grey
Tripod Mount	Bottom (isolated) and top 1/4-inch 20 UNC
Environmental	
Operating Temperature	-20°C to +50°C (-4°F to 122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Operating Humidity	20% to 93% RH
Storage Humidity	up to 98% RH
Power	
Power connector (VBC-265-11, VBC-265-11C)	Push type connectors, polarity independent, isolated from video output terminals
Power connector (VBC-265-51)	2-wire power cord with Euro plug
Power connector (VBC-265-51C)	2-wire power cord with Chinese plug



### Notice

Lens is not included

Certifications and approvals	
Region	Certification
Europe	CE
Standards	
	FCC Part 15, Class B
	EN55022: Class B
	EN50130-4 Alarm Systems, Part 4
	EN60065
	IEC60068-2-27: Vibration - camera with 500 g (1.1 lb) lens
Ordering information	
VBC-265-11 Day/Night Camera, 12 VDC/ 24 VAC	VBC-265-11
VBC-265-51 Day/Night Camera, 230 VAC	VBC-265-51
VBC-265-11C Day/Night Camera, 12 VDC/ 24 VAC, China	VBC-265-11C
VBC-265-51C Day/Night Camera, 230 VAC, China	VBC-265-51C

### Represented by:

#### Americas:

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

#### Europe, Middle East, Africa:

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: +31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

#### Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

#### China:

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

#### America Latina:

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
al.securitysystems@bosch.com  
www.boschsecurity.com